



## Notified Body # 1020



Technický a zkušební ústav stavební Praha, s.p.,  
Prosecka 811/76a, 190 000 Praha 9 – Prosek.

## Report # 1020-CPR-040 051681

Manufacturer/Production plant:

**World Acoustic Group S.A.**  
59-101 Polkowice, ul. Royal 1  
Poland

15

Product in compliance with requirements of norm.

### EN 14388:2005/AC:2008

Norm title: Road anti-noise equipment. Specification.

- Description:** Acoustic panels designed to be mounted free-standing acoustic screens , as a filling between the columns supporting the screen. Panels prevent direct propagation in airborne noise.
- Trade name of product:** Acoustic panel both side reflective

### WNR B - WAG Noise REFLECTOR type B

3. **Major properties:**

	Property	Declared value	Harmonized specification
1.	Airborne sound absorption:	DLR=21 dB (category B2)	EN 1793-1
3.	Max. wind load and static load	1,95 kN/m <sup>2</sup> (for length up to 4m) 1,65 kN/m <sup>2</sup> (for length up to 5m)	EN 1794-1:2003, Att. A
4.	Dead weight when dry	13,05 kg/m <sup>2</sup>	EN 1794-1: 2003 Att. B
5.	Dynamic load at plowing	15,0 kN/2mx2m (for length up to 5m)	EN 1794-1:2003 Att. E
6.	Resistance to a stone strike	Compliance with requirements	EN 1794-1:2003 Att. C
7.	Resistance to fire of bushes	Class 3	EN 1794-2:2003 Att. A
8.	Environmental protection	Recycling 100%	EN 1794-2:2003 Att. C
9.	Escape routes	Compliance with requirements	EN 1794-2:2003 Att. D
10.	Reflection of light	NPD	EN 1794-2:2003 Att. E
11.	Transparentness	NPD	EN 1794-2:2003 Att. F
12.	Durability of acoustic properties	- Changing the sound reflections DLRI after 5, 10, 15, 20 years: -1, -2, -3, -5 dB - Changing airborne sound insulation DL <sub>st</sub> after 5, 10, 15, 20 years: -1, -2, -3, -4 dB	EN 14389-1
13.	Durability of non-acoustic properties	Not less than 15 lat	EN 14389-2:2004



**WAG S.A.**

WORLD ACOUSTIC GROUP